



GBMA Bearing Manufacturing Co.,Ltd



6330/C3VL2071 Bearing 2D drawings and 3D CAD models

6330/C3VL2071 SKF Insulated Bearings

Bearing No. 6330/C3VL2071

Size	320x150x65 mm
Bore Diameter	320 mm
Outer Diameter	150 mm
Width	65 mm
d	150 mm
D	320 mm
B	65 mm
d ₁	205.6 mm
D ₁	263.4 mm
r _{1,2} - min.	4 mm
d _a - min.	167 mm
d _a - max.	200 mm
D _a - max.	303 mm
r _a - max.	3 mm
Basic dynamic load rating - C	276 kN
Basic static load rating - C ₀	285 kN
Fatigue load limit - P _u	7.8 kN
Reference speed	4300 r/min
Limiting speed	2800 r/min
Calculation factor - k _r	0.03
Calculation factor - f ₀	14
Category	Single Row Ball Bearings
Inventory	29.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



GBMA Bearing Manufacturing Co.,Ltd

Weight / Kilogram	23.05
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Electrical Insulation on Inner Ring
Cage Material	Steel
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	150MM Bore; 320MM Outside Diameter; 65MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Electrical Insulation on Inner Ring Internal Special Features; C3-Loose I
Other Features	Deep Groove VL2071 INSOCOAT Bearing with Coated Inner Ring
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	6330/C3VL2071
Weight / LBS	50.772
Bore	5.906 Inch 150 Millimeter
Outer Race Width	2.559 Inch 65 Millimeter
Inner Race Width	0 Inch 0 Millimeter



GBMA Bearing Manufacturing Co.,Ltd

Outside Diameter	12.598 Inch 320 Millimeter
bore diameter:	150 mm
static load capacity:	285 kN
outside diameter:	320 mm
finish/coating:	Uncoated
overall width:	65 mm
bearing material:	Steel
bore type:	Round
cage material:	Steel
closure type:	Open
fillet radius:	4 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	4300 rpm
snap ring included:	Without Snap Ring
weight:	50.5 lbs
internal clearance:	C3
manufacturer product page:	Click here
operating temperature range:	-40 to 212 ° F ° F
manufacturer upc number:	7316572206775
dynamic load capacity:	276 kN
d_1	205.6 mm
D_1	263.4 mm
$r_{1,2}$ min.	4 mm
d_a min.	167 mm
d_a max.	200 mm
D_a max.	303 mm
r_a max.	3 mm
Basic dynamic load rating C	276 kN
Basic static load rating C_0	285 kN
Fatigue load limit P_u	7.8 kN
Calculation factor k_r	0.03
Calculation factor f_0	13.9



GBMA Bearing Manufacturing Co.,Ltd

Mass bearing	23 kg
--------------	-------